## PCI 16-Relay / 16-Photo-Isolator



Item-No.: Relop-16P

Produktcode Taiwan:

APCI16P/R PCI 16 PHOTO/RELAY W/CE + Cable ifc37f40x35c

Label on the card:

PCI 16 PHOTO INPUT/ RELAY OUTPUT BOARD DCI2K04010301

Bus: 32 bits PCI bus with Plug and Play (PnP) features.

Description:

Support 16 relay output channels and 16 photo couple input channels

Max contact rating for relay: 70V/AC, 100V/DC 0.25AMP

Response time for relay: 1 ms minimum.

Contact resistance for relay: 0.2 OHM maximum.

Support several operating modes that are programmable.

16 Optoisolator input - Isolation 500 V max

High 2-30 V or 17-30 V by jumper

Features:

Flat cable with 37 pins connector is included

Software/Driver:

English manual with adjusting plan, terminal diagram, data sheets and sample programs Windows-98/NT/2000/XP,Vista, Win-7/8/10, Linux driver or info

Per shipping you receive freshly burned "Decision Computer Germany service CD" with current drivers, manuals, installation guidances and German additional information. The extent depends on the product!

**Operating temperature range:** from 0 to 55C. **Relative humidity rage:** from 0 to 90%.

Package includes the following items:

RELOP-16 Board,

Flat cable with 37 pins connector.

Software-CD, Manual

**Size:** 200 mm x 100 mm

Weight (Shipping): 500 Gram Weight (WEEE): 190 Gram



Decision-Computer Jürgen Merz e.K.

Lengericher Str. 21 49536 Lienen Deutschland Telefon ++49 (0) 5483-77002 Telefax ++49 (0) 5483-77003

jm@decision-computer.de www.decision-computer.de

